



- A = BLADE TIP THICKNESS @ 25° BLADE TIP ANGLE
- B = RUNNING POSITION OF BLADES
- C = MAXIMUM DROOP POSITION OF BLADES
- D = MINIMUM OBSTACLE CLEARANCE AT INLET
- G = BUSHING OVERALL HEIGHT
- H = MINIMUM OBSTACLE CLEARANCE AT OUTLET
- I = NOMINAL MECHANICAL HUB DIAMETER
- L = MAX. BUSHING TORQUE FT. LBS.
- # = WITH S.A.E. STANDARD SQUARE KEYWAY
- * = WITH SHALLOW KEYWAY IN BUSHING

NOTE 1:
 MAXIMUM FAN DIAMETER (BLADES HORIZONTAL - AS SHIPPED) EQUALS NOMINAL FAN DIAMETER. ADJUSTMENT OF -.25 INCHES POSSIBLE AT INSTALLATION.
FANS WITH ATEX TIPS HAVE NO INWARD ADJUSTMENT.

12000 FT:MIN BLADE TIP SPD	
PERCENT	
BLADE LOADING	
100%	75%

DIA	A	B		C	D	H
3'	8.6"	3.5"	3.5"	5.5"	2.0"	7.0"
4'	8.2"	3.9"	3.9"	5.9"	2.0"	7.0"
5'	7.8"	4.3"	4.3"	6.3"	2.0"	7.0"
6'	7.4"	4.8"	4.8"	6.8"	2.0"	7.0"

MAX BLADES	BUSHING TYPE	MAX # BORE	MAX * BORE	I	G	L
5	T	2.000"	2.188"	6"	1.9"	2000



SERIES 12 STANDARD HUB HD FAN RIGHT HAND ROTATION